



VMS Software

VSI Datatrieve Version T7.4-4 (Field Test) Release Notes

Publication Date: July 2026

Operating Systems: VSI OpenVMS x86-64 Version 9.2-3 or higher
VSI OpenVMS IA-64 Version 8.4-2L1 or higher

Software Version: VSI Datatrieve Version T7.4-4

VSI Datatrieve Version T7.4-4 (Field Test) Release Notes



Copyright © 2026 VMS Software, Inc. (VSI), Boston, Massachusetts, USA

Legal Notice

Confidential computer software. Valid license from VSI required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

The information contained herein is subject to change without notice. The only warranties for VSI products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. VSI shall not be liable for technical or editorial errors or omissions contained herein.

All other trademarks and registered trademarks mentioned in this document are the property of their respective holders.

1. Introduction

VSI is pleased to introduce the field test of VSI Datatrieve T7.4-4 for VSI OpenVMS x86-64 and OpenVMS IA-64.

VSI Datatrieve is a tool for managing information. It is a high-level interactive query and report generation tool. Datatrieve works against flat files, indexed files, and databases. Such data files are delimited using record definitions stored in the VSI Data Dictionary (VDD).

This document outlines the changes made to Datatrieve after its porting to OpenVMS x86-64 and OpenVMS IA-64, including the introduction of support for VDD.

2. Requirements

VSI Datatrieve T7.4-4 can be installed by a suitably privileged user on an OpenVMS system that meets the following minimum software requirements:

- One of the following versions of VSI OpenVMS:
 - VSI OpenVMS x86-64 Version 9.2-3 or higher
 - VSI OpenVMS IA-64 Version 8.4-2L1 or higher
- One of the following dictionary environments:
 - OpenVMS x86-64 requires VDD Version X1.2-03
 - OpenVMS IA-64 supports either VDD Version X1.2-03 or CDD

If using VDD, the user environment must be set up as follows:¹

1. Run the `SY$STARTUP$VDD$STARTUP.COM` and `SY$MANAGER:VDD$SETUP_USER_ENV.COM` command procedures:

```
$ @SY$STARTUP$VDD$STARTUP.COM
$ @SY$MANAGER:VDD$SETUP_USER_ENV.COM
```

2. Define the `VDD$DEFAULT` logical name to any valid VDD repository from the VSI VDD E1.2 release or later.

In the following example, `SY$COMMON:[SYSTEMREPO]` is used:

```
$ DEFINE VDD$DEFAULT SY$COMMON:[SYSTEMREPO]
```

3. Installing Datatrieve

Before installing VSI Datatrieve T7.4-4, ensure that the appropriate dictionary environment has been installed and configured as described in *Section 2, "Requirements"*.

If using VDD, ensure that the VDD environment has been set up as outlined [above](#). Then, run the command below from a privileged account (such as the `SYSTEM` account).

¹Ensure that these conditions are satisfied whenever you intend to use Datatrieve. Without them, Datatrieve will not work.

```
$ @SYS$UPDATE:VMSINSTAL * device-name:[username.DATATRIEVE]
```

The installation will then proceed as follows (output may differ slightly from that shown below depending on various factors):

```
OpenVMS Software Product Installation Procedure V9.2-3
```

```
It is 01-JUL-2026 at 10:38.
```

```
Enter a question mark (?) at any time for help.
```

```
* Are you satisfied with the backup of your system disk [YES]?
```

The following products will be processed:

```
DTRA V7.4
```

```
Beginning installation of DTRA V7.4 at 10:38
```

```
No signature manifests found for DTRA074
```

```
* Do you want to install this product [NO]? Yes
```

```
%VMSINSTAL-I-RESTORE, Restoring product save set A ...
```

```
%VMSINSTAL-I-REMOVED, Product's release notes have been moved to SYS$HELP.
```

```
DATATRIEVE T7.4-4 Installation Procedure
```

```
© Copyright 2026 VMS Software, Inc. and Hewlett-Packard Enterprise Development LP
```

```
* Do you want support for VDD (VSI Data Dictionary) [YES]?
```

```
NCP or NCL cannot be run.
```

```
Therefore, the DECnet object number for DDMF cannot be defined.  
To define a DDMF object number in the future, see the DATATRIEVE  
Installation Guide section on DECnet Considerations.
```

```
Product:      DTR or DTR-USER
```

```
Producer:     VSI
```

```
Version:      T7.4-4
```

```
Release Date: 01-JUL-2026
```

```
* Does this product have an authorization key registered and loaded? Yes
```

```
* Do you want to use default answers for all questions [YES]?
```

```
*****
```

```
The Language-Sensitive Editor is not installed on your  
system. To have the Language-Sensitive Editor support,  
you must:
```

1. Install the Language-Sensitive Editor
2. Install or reinstall this product

```
*****
```

```
* Do you want to continue the installation [NO]? Yes
```

```
The DATATRIEVE IVP will be put in the SYS$COMMON:[SYSTEST.DTR]  
directory. You may run the IVP immediately after the completion of
```

the installation procedure answering YES to the next question or later issuing the following command:

```
@SYS$COMMON:[SYSTEST.DTR]DTR$IVP.COM DTR32.EXE
```

- * Do you want to run the IVP after the installation [YES]? Yes
- * Proceed with this installation [YES]?

All questions regarding the installation have now been asked.

```
%VMSINSTAL-I-RESTORE, Restoring product save set B ...
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR].
%CREATE-I-EXISTS, VMI$ROOT:[DTR] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:
[SYSTEST.DTR].
%CREATE-I-EXISTS, VMI$ROOT:[SYSTEST.DTR] already exists
```

During the installation, a file called
DTRSTUP.COM has been added to SYS\$STARTUP:

The site-dependent start-up file, SYS\$MANAGER:SYSTARTUP.COM
should have the following line added:

```
$ @SYS$STARTUP:DTRSTUP.COM
```

```
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.ADT].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.ADT] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.DEMO].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.DEMO] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.FORMS].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.FORMS] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.GUIDE].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.GUIDE] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.PLOTS].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.PLOTS] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.DEMO.RDB].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.DEMO.RDB] already exists
%VMSINSTAL-I-SYSDIR, This product creates system disk directory VMI$ROOT:[DTR.DTR
$LIB.DEMO.DBMS].
%CREATE-I-EXISTS, VMI$ROOT:[DTR.DTR$LIB.DEMO.DBMS] already exists
```

```
*****
DATATRIEVE User Environment Test Packages (UETPs)
have been provided and can be run after the installation is
complete. They are invoked from DATATRIEVE as follows:
```

```
DTR> @sys$common:[sytest.dtr]dtr      ! The general test
DTR> @sys$common:[sytest.dtr]plots    ! The plots test
DTR> @sys$common:[sytest.dtr]rdb      ! The Rdb test
DTR> @sys$common:[sytest.dtr]forms    ! The Forms test
```

Before invoking these files from a user's account you must
execute the procedure :

```
@DTR$LIBRARY:NEWUSER.COM
```

This procedure loads the DATATRIEVE definitions into the

user's dictionary and the data files in the user's directory.
This procedure must be executed by each user needing
the DATATRIEVE examples

Restoring UETP-related Oracle Rdb objects

The following error messages may be safely ignored:

```
%RMU-I-AIJRSTAVL, 0 after-image journals available for use
%RMU-I-AIJISOFF, after-image journaling has been disabled
%RMU-W-USERECCOM, Use the RMU Recover command.
%CDD-I-MBLRSYNINFO, unsupported entity - marked Incomplete
```

A database for the DATATRIEVE UETP that utilizes Oracle Rdb
cannot be created because the Rdb monitor is not running.
Although the installation has not been aborted, the UETP will
not function properly. It is recommended that you start the
Oracle Rdb monitor then re-run this installation.

Cleanup the UETP-related Oracle Rdb objects

%VMSINSTAL-I-MOVEFILES, Files will now be moved to their target directories...

DATATRIEVE T7.4-4 Installation Procedure

© Copyright 2026 VMS Software, Inc. and Hewlett-Packard Enterprise Development LP

Executing IVP for: DATATRIEVE T7.4-4

© Copyright 2026 VMS Software, Inc. and Hewlett-Packard Enterprise Development LP

Test completed successfully

IVP COMPLETED SUCCESSFULLY

IVP completed for: DATATRIEVE T7.4-4

Installation of DTRA V7.4 completed at 10:40

Adding history entry in VMI\$ROOT:[SYSUPD]VMSINSTAL.HISTORY

Creating installation data file: VMI\$ROOT:[SYSUPD]DTRA074.VMI_DATA

VMSINSTAL procedure done at 10:41

VSI Datatrieve has now been successfully installed on your system.

4. Known Issues and Limitations

The following issues and limitations have been discovered at the time of this field test:

ACL-Related Commands

When Datatrieve is used with VDD, commands related to privileges are not supported because VDD does not currently provide ACL functionality. As a result, Datatrieve privilege-related commands will fail if used. For example:

```
DTR> SHOWP YACHTS
%VDD-E-INTERR1, internal error:
```

The affected commands are **DEFINEP**, **DELETEP**, and **SHOWP**.

Note

These commands function correctly when Datatrieve is run with CDD.

Executing CDO Commands From Datatrieve

When Datatrieve is used with VDD, the Datatrieve **CDO** command (which allows users to execute CDO commands from inside Datatrieve) is not supported and will fail if used. For example:

```
DTR> CDO DIRECTORY
internal error: !AF
%VDD-E-INTERR1, internal error:
```

Commands can instead be run by exiting Datatrieve and executing them directly in VDO.

Note

This command functions correctly when Datatrieve is run with CDD.

Protocol Usage

CDD supports two protocols, NAD and DMU. When Datatrieve is used with CDD, either protocol may be used.

VDD supports only the DMU protocol. As a result, when Datatrieve is used with VDD, it always operates using the DMU protocol.

This difference has minimal impact for the user, as the results from both protocols are mostly the same.